

Seamless, low-profile and high-quality.

Dynaudio Custom Performance in-ceiling speakers twist-fit without tools and adjust in seconds for tailored audio throughout the home.

Performance series In-ceiling






DYNAUDIO

Performance series

In-ceiling

- 2-way systems
- Ranging from 6.5 Inch to 8 Inch.
- Direct the sound towards you via pivoting tweeters
- EQ Adjustments for the tweeter
- Magnetic paintable round Grille. Square Grille as accessory
- Easy turn and click installation (tool less)
- Shallow speakers with high performance
- MSP woofer cone
- 1" Silk dome

Model number / in-ceiling	P4-C65	P4-DVC65	P4-C80
			
Type	2-way in-ceiling	2-way in-ceiling	2-way in-ceiling
Drivers	Tweeter: 28mm (1in); mid/bass: 165mm (6½in)	2x tweeter: 28mm (1in); mid/bass: 165mm (6½in)	Tweeter: 28mm (1in); mid/bass: 200mm (8in)
Performance frequency response (+/- 3dB)	55Hz–20kHz	50Hz–20kHz	45Hz–20kHz
Impedance (nominal/minimum)	8Ω / 5Ω	2x 4Ω / 2x 3.2Ω	8Ω / 5Ω
Sensitivity (dB SPL [2.83V/1m])	87.5dB	83.5dB	89dB
Rated power*	50W	2x 25W	60W
Long term power*	100W	2 x 50W	100W
Tweeter level options	-3dB, 0dB, +3dB	-3dB, 0dB	-3dB, 0dB, +3dB
Tweeter orientation	Pivoting 360*	Fixed	Pivoting 360*
Dimensions/depth	Ø232mm / 70mm (9¼in / 2¾in)	Ø232mm / 70mm (9¼in / 2¾in)	Ø280mm / 87mm (11in / 3½in)
Cut-out dimensions	Ø 210mm (8¼in)	Ø 210mm (8¼in)	Ø 260mm (10¼in)
Grille material	Painted steel	Painted steel	Painted steel
Grille options	Round (supplied) / square	Round (supplied) / square	Round (supplied) / square
Grille attachment	Magnetic	Magnetic	Magnetic
Grille finish	White (paintable)	White (paintable)	White (paintable)
Certifications	CE	CE	CE
Environmental	RoHS	RoHS	RoHS

* Power handling according to IEC268. Rated power is continuous power for 100 hours.