

ELAC Debut 2.0

ELAC The life of sound.

Debut A4.2

A4.2 SPECIFICATIONS

SPEAKER TYPE	Sealed, 2-way concentric
FREQUENCY RESPONSE	180 to 20,000 Hz
NOMINAL IMPEDANCE	6 Ω
SENSITIVITY	85 dB at 2.83 v/1m
CROSSOVER FREQUENCY	2,000 Hz
MAXIMUM POWER INPUT	80 Watts
TWEETER	.5-inch polymer dome
WOOFER	4-inch woven aramid-fiber cone with oversized magnet
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
BINDING POSTS	5-way metal
WIDTH	7.09 in / 180 mm
HEIGHT	4.92 in / 125 mm
DEPTH	9.21 in / 234 mm
WEIGHT	5.416 lb / 2.4 kg



Debut A4.2

Debut Sub 3010

SUB3010 SPECIFICATIONS

SPEAKER TYPE	Powered bass-reflex subwoofer
AMPLIFIER TYPE	BASH—Tracking
MAXIMUM AMPLIFIER POWER	400 Watts peak / 200 Watts RMS
FREQUENCY RESPONSE	28 to 150 Hz
CROSSOVER FREQUENCY	50 to 150 Hz, continuously adjustable
DRIVER	10-inch high-excursion doped paper cone
PASSIVE RADIATOR	10-inch high-excursion doped paper cone
STANDBY POWER CONSUMPTION	1 Watt
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
INPUTS	2 x RCA (L, R / LFE)
DATA CONNECTION	USB (Firmware Update)
APP CONTROL	iOS and Android
WIDTH	14.33 in / 364 mm
HEIGHT	13.5 in / 343 mm
DEPTH	13.5 in / 343 mm
WEIGHT	32.1 lb / 14.5 kg



Debut SUB 3010



Debut OW4.2

Debut OW4.2 On-Wallspeaker

OW4.2 SPECIFICATIONS

SPEAKER TYPE	2-way, bass reflex
FREQUENCY RESPONSE	70 to 35,000 Hz
NOMINAL IMPEDANCE	6 Ω
SENSITIVITY	87 dB at 2.83 v/1m
CROSSOVER FREQUENCY	2,500 Hz
MAXIMUM POWER INPUT	80 Watts
TWEETER	1-inch cloth dome
WOOFER	4-inch woven aramid-fiber cone with oversized magnet
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
BINDING POSTS	5-way metal
WIDTH	7.87 in / 200 mm
HEIGHT	12.76 in / 324 mm
DEPTH	3.94 / 100 mm
WEIGHT	7.9 lb / 3.6 kg

Everything we do
is different

ELAC Debut by Andrew Jones.




ELAC Debut 2.0


Redesigned from the ground up, these speakers sound even more remarkable than the ones that sparked the revolution in aordable high-end sound.



Woven Aramid-Fiber Woofer
Woven aramid fiber offers a superior stiffness-to-weight ratio and damping over common polypropylene or paper cones.



All-New Design - All-New Debut!
Everything about Debut 2.0 has been improved, including completely redesigned custom drivers that deliver greater accuracy, and robust cabinets for even higher resolution and freedom from resonances.



Advanced Bluetooth® Control
Doing away with traditional analog controls, the SUB3010 incorporates our advanced digital control system.

Few speakers have garnered such critical acclaim as the original Debut Series by ELAC. They established a new value proposition, with build quality and performance never before attainable at such an affordable price. Debut “changed the game,” and has now changed it again with the Debut 2.0 Series—proof that ELAC can’t leave well enough alone.

ELAC Debut by Andrew Jones.

Debut B5.2 Bookshelfspeaker

B5.2 SPECIFICATIONS

SPEAKER TYPE	2-way, bass reflex
FREQUENCY RESPONSE	46 to 35,000 Hz
NOMINAL IMPEDANCE	6 Ω
SENSITIVITY	86 dB at 2.83 v/1m
CROSSOVER FREQUENCY	2,200 Hz
MAXIMUM POWER INPUT	120 Watts
TWEETER	1-inch cloth dome
WOOFER	5.25-inch woven aramid-fiber cone with oversized magnet and vented pole piece
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
PORT	Dual flared
BINDING POSTS	5-way metal
WIDTH	7.09 in / 180 mm
HEIGHT	13.43 in / 341 mm
DEPTH	9.21 in / 234 mm
WEIGHT	13.0 lb / 5.9 kb



Debut B5.2

Debut C5.2 Centerspeaker

C5.2 SPECIFICATIONS

SPEAKER TYPE	2-way, bass reflex
FREQUENCY RESPONSE	55 to 35,000 Hz
NOMINAL IMPEDANCE	8 Ω
SENSITIVITY	87 dB at 2.83 v/1m
CROSSOVER FREQUENCY	2,200 Hz
MAXIMUM POWER INPUT	120 Watts
TWEETER	1-inch cloth dome
WOOFER	2 x 5.25-inch woven aramid-fiber cones with oversized magnet and vented pole piece
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
PORTS	2 x dual flared
BINDING POSTS	5-way metal
WIDTH	21.25 in / 540 mm
HEIGHT	7.09 in / 180 mm
DEPTH	8.62 in / 219 mm
WEIGHT	18.3 lb / 8.3 kb



Debut C5.2

Debut F5.2 Floorstandingspeaker

F5.2 SPECIFICATIONS

SPEAKER TYPE	3-way, bass reflex
FREQUENCY RESPONSE	42 to 35,000 Hz
NOMINAL IMPEDANCE	6 Ω
SENSITIVITY	86 dB at 2.83 v/1m
CROSSOVER FREQUENCIES	90 Hz / 2,200 Hz
MAXIMUM POWER INPUT	140 Watts
TWEETER	1-inch cloth dome
WOOFER	3 x 5.25-inch woven aramid-fiber cones with oversized magnet and vented pole piece
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
PORTS	3 x dual flared
BINDING POSTS	5-way metal
WIDTH	7.09 in / 180 mm
HEIGHT	40.0 in / 1016 mm
DEPTH	9.21 in / 234 mm
WEIGHT	34.4 lb / 15.6 kg



Debut F5.2

Debut B6.2 Bookshelfspeaker

B6.2 SPECIFICATIONS

SPEAKER TYPE	2-way, bass reflex
FREQUENCY RESPONSE	44 to 35,000 Hz
NOMINAL IMPEDANCE	6 Ω
SENSITIVITY	87 dB at 2.83 v/1m
CROSSOVER FREQUENCY	2,200 Hz
MAXIMUM POWER INPUT	120 Watts
TWEETER	1-inch cloth dome
WOOFER	6.5-inch woven aramid-fiber cone with oversized magnet and vented pole piece
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
PORT	Dual flared
BINDING POSTS	5-way metal
WIDTH	7.69 in / 195 mm
HEIGHT	14.76 in / 375 mm
DEPTH	10.55 in / 268 mm
WEIGHT	16.3 lb / 7.4 kg



Debut B6.2

Debut F6.2 Floorstandingspeaker

F6.2 SPECIFICATIONS

SPEAKER TYPE	3-way, bass reflex
FREQUENCY RESPONSE	39 to 35,000 Hz
NOMINAL IMPEDANCE	6 Ω
SENSITIVITY	87 dB at 2.83 v/1m
CROSSOVER FREQUENCIES	90 Hz / 2,200 Hz
MAXIMUM POWER INPUT	140 Watts
TWEETER	1-inch cloth dome
WOOFER	3 x 6.5-inch woven aramid-fiber cones with oversized magnet and vented pole piece
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
PORTS	3 x dual flared
BINDING POSTS	5-way metal
WIDTH	7.69 in / 195 mm
HEIGHT	43.18 in / 1097 mm
DEPTH	10.55 in / 268 mm
WEIGHT	43.9 lb / 19.9 kg



Debut C6.2



Debut F6.2

Debut C6.2 Centerspeaker

C6.2 SPECIFICATIONS

SPEAKER TYPE	2-way, bass reflex
FREQUENCY RESPONSE	55 to 35,000 Hz
NOMINAL IMPEDANCE	8 Ω
SENSITIVITY	88 dB at 2.83 v/1m
CROSSOVER FREQUENCY	2,200 Hz
MAXIMUM POWER INPUT	120 Watts
TWEETER	1-inch cloth dome
WOOFER	2 x 6.5-inch woven aramid-fiber cones with oversized magnet and vented pole piece
CABINET	CARB2 rated MDF
CABINET FINISH	Black Ash vinyl
PORTS	2 x dual flared
BINDING POSTS	5-way metal
WIDTH	23.35 in / 593 mm
HEIGHT	7.61 in / 193 mm
DEPTH	10.55 in / 268 mm
WEIGHT	25.4 lb / 11.5 kg