

elipson® | Prestige Facet II 14F

ENCEINTE COLONNE - 2 ½ VOIES - BASS-REFLEX



Avec la Prestige Facet 14F II, Elipson sublime sa colonne emblématique en intégrant les dernières évolutions de la gamme Facet II.

Toujours fidèle à la philosophie d'origine — neutralité, musicalité et précision — cette nouvelle génération bénéficie de perfectionnements acoustiques majeurs pour repousser encore les limites de la fidélité.

Dotée d'une configuration 2 ½ voies, elle combine un tweeter à dôme souple de 25 mm, un haut-parleur grave-médium et un grave de 170 mm chacun pour délivrer une restitution sonore ample et dynamique.





TECHNIQUE

Type Enceinte colonne - 2 ½ voies - Bass-reflex	Filtre répartiteur- Fc 600 & 2500 Hz - 12 dB / 12 dB / 18 dB
Puissance 150 W RMS	Impédance nominale 6 Ω
Amplification recommandée 40 - 200 W	Impédance minimale 4,5 Ω @ 220 Hz
Haut-parleurs Tweeter : 25 mm Grave-médium : 170 mm Grave : 170 mm	Fréquence d'accord bass-reflex 35 Hz
Réponse en fréquence (±3dB) 38 Hz - 25 kHz	Bornier Argentés pour bi-câblage ou bi-amplification
Sensibilité 92 dB / 1W / 1m	

DIMENSIONS
POIDS

Dimensions sans/avec pieds L207 x H990 / L1030 x P303 mm	Poids sans/avec pieds 19,7 kg / 20,2 kg
Espace d'encombrement L276 x P359 mm	

PACKAGING

Packaging dimensions L425 x H1150 x P340 mm	Poids brut 23,8 kg
---	------------------------------

FINITIONS
-
CODES
PRODUITS

	Finition Noir mat	SKU ELIPF214FMBK	EAN 3700795194522
	Finition Blanc mat	SKU ELIPF214FMWT	EAN 3700795194539
	Finitions Noir mat - Noyer	SKU ELIPF214FWNBK	EAN 3700795194546

elipson® | Prestige Facet II 14F

FLOORSTANDING LOUDSPEAKER - 2 ½ WAY - BASS-REFLEX



With the Prestige Facet 14F II, Elipson sublimates its emblematic column by integrating the latest developments in the Facet II range.

Still faithful to the original philosophy - neutrality, musicality and precision - this new generation benefits from major acoustic improvements to push back the limits of fidelity even further.

Featuring a 2 ½-way configuration, it combines a 1" soft dome tweeter, a 7" bass-midrange driver and a 7" bass driver to deliver a full, dynamic sound reproduction.





TECHNICAL

Type Floorstanding loudspeaker - 2 ½ way - Bass-reflex	Crossover 600 & 2500 Hz - 12 dB / 12 dB / 18 dB
Power 150 W RMS	Nominal impedance 6 Ω
Power amplifier 40 - 200 W	Minimum Impedance 4,5 Ω @ 220 Hz
Drive-Units Tweeter : 1" Mid-woofer : 7" Woofer : 7"	Tuned bass-reflex frequency 35 Hz
Frequency response (±3dB) 38 Hz - 25 kHz	Terminals Silver plated for bi-wiring or bi-amplification
Sensitivity 92 dB / 1W / 1m	

DIMENSIONS
WEIGHTS

Dimensions without/with feet W207 x H990 / W1030 x D303 mm	Weight without/with feet 19,7 kg / 20,2 kg
Space requirements W276 x D359 mm	

PACKAGING

Packaging dimensions W425 x H1150 x D340 mm	Gross weight 23,8 kg
---	--------------------------------

FINISHES
-
PRODUCTS
CODES

	Finish Black matt	SKU ELIPF214FMBK	EAN 3700795194522
	Finish White matt	SKU ELIPF214FMWT	EAN 3700795194539
	Finishes Black matt - Walnut	SKU ELIPF214FWNBK	EAN 3700795194546